

DANGOTE POLYPROPYLENE

PP Homo Grade MSDS

MATERIAL SAFETY DATA SHEET

FIRST AID MEASURES

GENERAL INFORMATION

At room temperature the product is neither an irritant nor gives off hazardous vapors. The measures listed below apply to critical situations (Fire, incorrect process conditions).

Skin Contact

If molten material contacts the skin it may cause thermal burns, immediately flush with large amounts of cold water to cool the affected skin and polymer. Do not attempt to peel the polymer from skin. Obtain immediately emergency medical attention if burn is deep or extensive.

Eye Contact

Dust, fines and process vapours may irritate the eyes. Rinse immediately with plenty of water, also underthe eyelids, for at least 15 minutes. Seek medical attention if discomfort persists.

Inhalation

Dust and process vapours may irritate the nose, throat and respiratory tract. If symptoms are experienced, move victim to fresh air. Obtain medical attention if breathing difficulty persists.

Ingestion

Adverse health effects due to ingestion are not anticipated. Do not induce vomiting. If symptoms develop, obtain medical attention.